

Applied Testing & Geosciences, LLC

When Quality Counts

Standard Specification for Architectural Cast Stone

www.appliedtesting.com

Client:

Company Name Precast Stones NY Corp

Reported To Wilson Gordillo

Company Address 3275 Grace Avenue, Bronx, NY, 10469 3275 Grace Avenue, Bronx, NY, 10469 **Facility Location**

13135 Precast Stones NY Corp Project

3/20/23 Report Notes

Samples:

Chain of Custody Client-ID ATG-ID Description

COC-032923-13135-01 Concrete 5569-1 3/20/23 Concrete Block

Sampled Recv. By Received Method **Condition Store** Client 3/20/23 3/29/23 Random Intact Amb.

Photo:

5569-1 Concrete 3/20/23 Concrete

Block



Test Results:

ASTM	Description	Spec	Result	Units	C/NC
C1194	Avg. Comp. Strength (28 day)	≥6,500	10,065	psi	С
C1194	Comp. Strength Test Age	N/A	28	days	R
C1195	Avg. Absorption	≤6	4.3	%	С
C1195	Absorption Test Age	N/A	28	days	R

Statement of Conformity:

Tests (assigned C) conform to the referenced Spec value shown.

Test Date (Start - End): 3/29/23 - 4/17/23

TS Technician: Ryan A. Quitinsky

Thomas C. Smith TS Manager:

Gran Quitivous

Notes:

- 1. Equip No. / Calib: Balance (702) 3/31/24; Caliper 6" (3) 1/24/24; Thermometer Concrete (Lab Casting) (2093) - 8/23/23; 2. Technician Quals: C1194 - 1/3/28; C1195 - 1/3/28; C1364 - 1/3/28;
- 3. Chain of Custody on file.
- 4. Test Notes/Spec: Per Client / Standard(s) for applicable material(s).
- 5. Abbreviations: C=Conforms to Spec value shown, NC=Non-Conformance to Spec value shown, R=Report for Information only, NR=Not Requested by Client/Contract. Also see https://dms.appliedtesting.com/Download/abbreviations.pdf

END-OF-REPORT

- 6. Report may be reproduced or distributed only in its entirety.
- 7. Interpretation of test results is beyond the scope of this report. 8. Results apply to samples as received. Description per client.
- 9. Significance and use of test results per ASTM Standard.
- 10. Precision and bias of test results per ASTM Standard. 11. Test Location: 401 E. 4th St, Bridgeport PA 19405.
- 12. Decision Rule Simple acceptance used in conformance decisions. Guardband (w) set equal to zero (0). (No application of measurement uncertainty).